

MATERIAL SAFETY DATA SHEET

E-Z TOLUENE - TOLUOL

EMERGENCY CONTACT: FOR CHEMICAL EMERGENCY - SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT,
CALL CHEMTREC AT 1-(800)-424-9300, DAY OR NIGHT.

<u>INDEX</u>	<u>HMIS</u>	<u>NFPA</u>
4 - Extreme	Health *2	Health 2
3 - High	Flammability 3	Flammability 3
2 - Moderate	Physical Hazard 0	Reactivity 0
1 - Slight		
0 - Least		

* denotes chronic hazard

Section 2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>COMPONENT</u>	<u>CAS NO.</u>	<u>AMOUNT (VOL%)</u>
TOLUENE	108-88-3	100

EXPOSURE GUIDELINES (SEE SECTION 15 FOR ADDITIONAL EXPOSURE LIMITS)

	<u>CAS NO.</u>	<u>GOVERNING BODY</u>	<u>EXPOSURE LIMITS</u>
TOLUENE	108-88-3	OSHA	C 300 ppm
TOLUENE	108-88-3	Mfg	STEL 150 ppm
TOLUENE	108-88-3	NIOSH	STEL 150 ppm
TOLUENE	108-88-3	ACGIH	TWA 50 ppm
TOLUENE	108-88-3	OSHA	TWA 200 ppm

Section 3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Danger! Flammable liquid and vapor. Harmful or fatal if swallowed. Pulmonary aspiration hazard. After ingestion, may enter lungs and produce damage. Harmful if inhaled. High vapor concentrations may cause drowsiness. May cause skin irritation. Causes eye irritation. Can cause severe chronic toxicity.

POTENTIAL HEALTH EFFECTS

PRE-EXISTING MEDICAL CONDITIONS

The following diseases or disorders may be aggravated by exposure to this product: skin, eye, liver, kidney, nervous system, respiratory system, lung (asthma-like conditions).

INHALATION

Can cause severe central nervous system depression (including unconsciousness). May cause headaches and dizziness. Vapors irritating to eyes and respiratory tract. Prolonged or repeated exposure may cause liver and kidney damage. Solvent "huffing/sniffing" (abuse) or intentional prolonged overexposure to high levels of vapors can produce abnormal behavior, convulsions, hallucinations, delirium, nervous system damage, serious disturbances of heart rhythm and sudden death.

LC50 (mg/l):	no data
LC50 (mg/m3):	no data
LC50 (ppm):	no data

SKIN

May be absorbed through the skin in harmful amounts. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Prolonged or repeated skin contact may cause irritation. Skin absorption of material may produce systemic toxicity.

Draize Skin Score:	no data	out of 8.0
LD50 (mg/kg):	no data	

EYES

Mildly irritating to the eyes.

INGESTION

Product may be harmful or fatal if swallowed. Pulmonary aspiration hazard. After ingestion, may enter lungs and produce damage. May produce central nervous system effects, which may include dizziness, loss of balance and coordination, unconsciousness, coma and even death. Irritating to mouth, throat and stomach.

LD50 (g/kg):	no data
--------------	---------

Section 4. FIRST AID MEASURES

INHALATION

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and continue to monitor. Get immediate medical attention.

SKIN

Wash with soap and water. Get medical attention if irritation develops or persists. Wash clothing before reuse.

EYES

Flush eye with water for 15 minutes. Get medical attention.

INGESTION

Do not induce vomiting! Do not give liquids! Get medical attention immediately.

Section 5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Water spray, regular foam, dry chemical, carbon dioxide

FIRE FIGHTING INSTRUCTIONS

Use water spray. Use water spray to cool fire exposed tanks and containers. Wear structural fire fighting gear.

FLAMMABLE PROPERTIES

	<u>TYPICAL</u>	<u>MINIMUM</u>	<u>MAXIMUM</u>	<u>TEXT RESULT</u>	<u>UNITS</u>	<u>METHOD</u>
Flash Point	48				F	N/A
Autoignition Temperature	997				F	N/A
Lower Explosion Limit	1.2				%	N/A
Upper Explosion Limit	7.1				%	N/A

Section 6. ACCIDENTAL RELEASE MEASURES

Prevent ignition, stop leak and ventilate the area. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Vapor can be controlled using a water fog. Water streams should not be directed to the liquid as this will cause the liquid to boil and generate more vapor. Keep personnel upwind from leak. Use appropriate personal protective equipment as stated in Section 8 of this MSDS. Advise the Environmental Protection Agency (EPA) and appropriate state agencies, if required. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Vacuum or sweep up material and place in a disposal container.

Section 7. HANDLING AND STORAGE

HANDLING

Use only in a well-ventilated area. Ground and bond containers when transferring material. Avoid breathing (dust, vapor, mist, gas). Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Wash thoroughly after handling.

STORAGE

Keep away from heat, sparks and flame. Store in a cool dry place. Keep container closed when not in use. NFPA class IB storage. Flash point is less than 73 degrees F and boiling point is greater than or equal to 100 degrees F. Consult NFPA and/or OSHA codes for additional information.

Section 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Consult With a Health and Safety Professional for Specific Selections

ENGINEERING CONTROLS

Use with adequate ventilation. Use explosion-proof ventilation equipment.

PERSONAL PROTECTION

EYE PROTECTION

Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

GLOVES or HAND PROTECTION

The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection. Protective gloves are recommended to protect against contact with product. Polyvinyl alcohol, viton, teflon

RESPIRATORY PROTECTION

Concentration in air determines the level of respiratory protection needed. Use only NIOSH certified respiratory equipment. Half-mask air purifying respirator with organic vapor cartridges is acceptable for exposures to ten (10) times the exposure limit. Full-face air purifying respirator with organic vapor cartridges is acceptable for exposures to fifty (50) times the exposure limit. Exposure should not exceed the cartridge limit of 1000 ppm. Protection by air

purifying respirators is limited. Use a positive pressure-demand full-face supplied air respirator or SCBA for exposures greater than fifty (50) times the exposure limit. If exposure is above the IDLH (Immediately Dangerous to Life and Health) or there is the possibility of an uncontrolled release, or exposure levels are unknown, then use a positive pressure-demand full-face supplied air respirator with escape bottle or SCBA. Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

OTHER

Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required. The following materials are acceptable for use as protective clothing: polyvinyl alcohol (PVA), viton, teflon. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Remove contaminated clothing and wash before reuse. For non-fire emergencies, positive pressure SCBA and structural firefighter's protective clothing will provide only limited protection.

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

<u>PHYSICAL PROPERTY</u>	<u>TYPICAL</u>	<u>UNITS</u>	<u>TEXT RESULT</u>	<u>REFERENCE</u>
Appearance		N/A	COLORLESS LIQUID	
Boiling Point	231	F		
Bulk Density		lb/gal	no data	
Melting Point		F	MINUS 139	
Molecular Weight	92.14	g/mole		
Octanol/Water Coefficient		N/A	no data	
pH		N/A	no data	
Specific Gravity	0.87	N/A		
Solubility in Water	0.047	wt%		
Odor		N/A	PLEASANT, SWEET ODOR	
Odor Threshold		ppm	no data	
Vapor Pressure	26	mmHg	@25C	
Viscosity (F)		SUS	no data	
Viscosity (C)		CsT	no data	
% Volatile	100	wt%		

Section 10. STABILITY AND REACTIVITY

STABILITY

Stable

CONDITIONS TO AVOID

Avoid static discharge. Avoid heat, sparks and open flame.

INCOMPATIBILITY

Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS

Combustion may produce carbon monoxide, carbon dioxide and other asphyxiants.

HAZARDOUS POLYMERIZATION

Will not polymerize.

Section 11. ECOLOGICAL INFORMATION

No data available

Section 12. DISPOSAL CONSIDERATIONS

Follow federal, state and local regulations. This material is a RCRA hazardous waste. Do not flush material to drain or storm sewer. Contract to authorized disposal service.

Section 13. TRANSPORT INFORMATION

<u>Governing Body</u>	<u>Mode</u>	<u>Proper Shipping Name</u>	<u>Container Mode</u>
DOT	Ground	Toluene, 3, UN1294, II	55 Gal Drum/5 Gal Pail/Gallon
IMDG	Marine	unknown	
IATA	Air	unknown	

<u>Governing Body</u>	<u>Mode</u>	<u>Proper Shipping Name</u>	<u>Container Mode</u>
DOT	Ground	Consumer Commodity, ORM-D	Quart
IMDG	Marine	unknown	
IATA	Air	unknown	

OTHER TRANSPORT INFORMATION

The DOT Transport Information may vary with the container and mode of shipment.

Section 14. REGULATORY INFORMATION

<u>Regulatory List</u>	<u>Component</u>	<u>CAS No.</u>
ACGIH-Occupational Exposure Limits-Carcinogens	TOLUENE	108-88-3
ACGIH-Occupational Exposure Limits-TWAs	TOLUENE	108-88-3
ACGIH-Skin Absorption Designation	TOLUENE	108-88-3
CAA (Clean Air Act)-HON Rule-Organic HAPs	TOLUENE	108-88-3
CAA (Clean Air Act)-HON Rule-SOCMI Chemicals	TOLUENE	108-88-3
CAA-1990 Hazardous Air Pollutants	TOLUENE	108-88-3
California-Prop. 65-Developmental Toxicity	TOLUENE	108-88-3
Canada-WHMIS: Ingredient Disclosure	TOLUENE	108-88-3
CERCLA/SARA-Haz Substances and their RQs	TOLUENE	108-88-3
CERCLA/SARA-Haz Substances and their RQs	TOLUENE	108-88-3
CERCLA/SARA-Haz Substances and their RQs	TOLUENE	108-88-3
CERCLA/SARA-Section 313-Emission Reporting	TOLUENE	108-88-3
CWA (Clean Water Act)-Hazardous Substances	TOLUENE	108-88-3
CWA (Clean Water Act)-Priority Pollutants	TOLUENE	108-88-3
CWA (Clean Water Act)-Toxic Pollutants	TOLUENE	108-88-3
IARC-Group 3 (not classifiable)	TOLUENE	108-88-3
Inventory-Australia (AICS)	TOLUENE	108-88-3
Inventory-Canada-Domestic Substances List	TOLUENE	108-88-3
Inventory-China	TOLUENE	108-88-3
Inventory-European EINECS Inventory	TOLUENE	108-88-3
Inventory-Japan-(ENCS)	TOLUENE	108-88-3
Inventory-Korea-Existing and Evaluated	TOLUENE	108-88-3
Inventory-Philippines Inventory (PICCS)	TOLUENE	108-88-3
Inventory-TSCA-Sect.8(b) Inventory	TOLUENE	108-88-3
Massachusetts-Right To Know List	TOLUENE	108-88-3
New Jersey-Department of Health RTK List	TOLUENE	108-88-3
New Jersey-Env Hazardous Substances List	TOLUENE	108-88-3
New Jersey-Special Hazardous Substances	TOLUENE	108-88-3
OSHA-Final PELs-Ceiling Limits	TOLUENE	108-88-3
OSHA-Final PELs-Time Weighted Averages	TOLUENE	108-88-3
Pennsylvania-RTK (Right to Know) List	TOLUENE	108-88-3

Title III Classifications Sections 311, 312:

Acute:	YES
Chronic:	YES
Fire:	YES
Reactivity:	NO
Sudden Release of Pressure:	NO

Section 15. OTHER INFORMATION

Follow all MSDS/label precautions even after container is emptied because it may retain product residue.

E.E. Zimmerman Company/Elroy Turpentine Company believes that the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.