

MATERIAL SAFETY DATA SHEET

E-Z XYLENE XYLOL

EMERGENCY CONTACT: FOR CHEMICAL EMERGENCY - SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT,
CALL CHEMTREC AT 1-(800)-424-9300, DAY OR NIGHT.

<u>INDEX</u>	<u>HMIS</u>	<u>NFPA</u>
4 - Extreme	Health *2	Health 2
3 - High	Flammability 3	Flammability 3
2 - Moderate	Physical Hazard 0	Reactivity 0
1 - Slight		
0 - Least		

* denotes chronic hazard

Section 2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>COMPONENT</u>	<u>CAS NO.</u>	<u>AMOUNT (VOL%)</u>
M-XYLENE	108-38-3	0-46
P-XYLENE	106-42-3	0-20
ETHYL BENZENE	100-41-4	0-19
O-XYLENE	95-47-6	0-15
TOLUENE	108-88-3	0-0.5
BENZENE	71-43-2	0-0.01

EXPOSURE GUIDELINES (SEE SECTION 15 FOR ADDITIONAL EXPOSURE LIMITS)

	<u>CAS NO.</u>	<u>GOVERNING BODY</u>	<u>EXPOSURE LIMITS</u>
Limit for the product	1330-20-7	ACGIH	STEL 150 ppm
Limit for the product	1330-20-7	ACGIH	TWA 100 ppm
Limit for the product	1330-20-7	OSHA	TWA 100 ppm
BENZENE	71-43-2	OSHA	C 5 ppm Ceiling
BENZENE	71-43-2	ACGIH	STEL 2.5 ppm
BENZENE	71-43-2	OSHA	STEL 5 ppm
BENZENE	71-43-2	ACGIH	TWA 0.5 ppm
BENZENE	71-43-2	OSHA	TWA 1 ppm
ETHYL BENZENE	100-41-4	ACGIH	STEL 125 ppm
ETHYL BENZENE	100-41-4	ACGIH	TWA 100 ppm
ETHYL BENZENE	100-41-4	OSHA	TWA 100 ppm
M-XYLENE	108-38-3	ACGIH	STEL 150 ppm
M-XYLENE	108-38-3	ACGIH	TWA 100 ppm
M-XYLENE	108-38-3	OSHA	TWA 100 ppm
O-XYLENE	95-47-6	ACGIH	STEL 150 ppm
O-XYLENE	95-47-6	ACGIH	TWA 100 ppm
O-XYLENE	95-47-6	OSHA	TWA 100 ppm
P-XYLENE	106-42-3	ACGIH	STEL 150 ppm
P-XYLENE	106-42-3	ACGIH	TWA 100 ppm
P-XYLENE	106-42-3	OSHA	TWA 100 ppm
TOLUENE	108-88-3	OSHA	C 300 ppm
TOLUENE	108-88-3	Mfg	STEL 150 ppm
TOLUENE	108-88-3	NIOSH	STEL 150 ppm
TOLUENE	108-88-3	ACGIH	TWA 50 ppm
TOLUENE	108-88-3	OSHA	TWA 200 ppm

Section 3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Danger! Flammable liquid and vapor. Harmful if inhaled. Overexposure may cause nervous system effects. May cause serious disturbances of heart rhythm. May cause skin irritation. Causes eye irritation. Causes respiratory tract irritation. Harmful or fatal if swallowed. Pulmonary aspiration hazard. After ingestion, may enter lungs and produce damage.

POTENTIAL HEALTH EFFECTS

PRE-EXISTING MEDICAL CONDITIONS

The following diseases or disorders may be aggravated by exposure to this product: skin, eye, liver, kidney, nervous system, respiratory system, lung (asthma-like conditions).

INHALATION

High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness and even death). Repeated overexposure has caused a hearing loss in laboratory animals. Repeated overexposure has produced toxic effects in developing and young laboratory animals. Solvent "huffing/sniffing" (abuse) or intentional prolonged overexposure to high levels of vapors can produce abnormal behavior, convulsions, hallucinations, delirium, nervous system damage, serious disturbances of heart rhythm and sudden death. Prolonged or repeated exposure may cause liver and kidney damage. See Section 15 for additional information.

LC50 (mg/l):	no data
LC50 (mg/m3):	no data
LC50 (ppm):	26800

SKIN

May be absorbed through the skin in harmful amounts. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Prolonged or repeated skin contact may cause irritation.

Draize Skin Score:	no data	out of 8.0
LD50 (mg/kg):	2000	

EYES

Causes eye irritation.

INGESTION

Moderately toxic. Irritating to mouth, throat and stomach. May produce central nervous system effects, which may include dizziness, loss of balance and coordination, unconsciousness, coma and even death. Product may be harmful or fatal if swallowed. Pulmonary aspiration hazard. After ingestion, may enter lungs and produce damage. See Section 15 for additional information.

LD50 (g/kg):	4.3
--------------	-----

Section 4. FIRST AID MEASURES

INHALATION

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and continue to monitor. Get immediate medical attention.

SKIN

Wash with soap and water. Get medical attention if irritation develops or persists. Wash clothing before reuse. Injection injuries may not appear serious at first but within a few hours, without proper treatment, the area will become swollen, discolored and extremely painful. See Section 15 for additional information.

EYES

Flush eye with water for 15 minutes. Get medical attention.

INGESTION

Do not induce vomiting! Do not give liquids! Get medical attention immediately.

Section 5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Water spray, regular foam, dry chemical, carbon dioxide

FIRE FIGHTING INSTRUCTIONS

Use water spray to cool fire exposed tanks and containers. Wear structural fire fighting gear.

FLAMMABLE PROPERTIES

	<u>TYPICAL</u>	<u>MINIMUM</u>	<u>MAXIMUM</u>	<u>TEXT RESULT</u>	<u>UNITS</u>	<u>METHOD</u>
Flash Point				79 TAG C.C.	F	N/A
Autoignition Temperature	870				F	N/A
Lower Explosion Limit	1.1				%	N/A
Upper Explosion Limit	6.6				%	N/A

Section 6. ACCIDENTAL RELEASE MEASURES

Prevent ignition, stop leak and ventilate the area. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Vapor can be controlled using a water fog. Water streams should not be directed to the liquid as this will cause the liquid to boil and generate more vapor. Keep personnel upwind from leak. Use appropriate personal protective equipment as stated in Section 8 of this MSDS. Advise the Environmental Protection Agency (EPA) and appropriate state agencies, if required. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Vacuum or sweep up material and place in a disposal container.

Section 7. HANDLING AND STORAGE

HANDLING

Use only in a well-ventilated area. Ground and bond containers when transferring material. Avoid breathing (dust, vapor, mist, gas). Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Wash thoroughly after handling. Never siphon by mouth.

STORAGE

Keep away from heat, sparks and flame. Store in a cool dry place. NFPA class IC storage. Flash point is greater than 73 degrees F and less than 100 degrees F. Consult NFPA and/or OSHA codes for additional information.

Section 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Consult With a Health and Safety Professional for Specific Selections

ENGINEERING CONTROLS

Use with adequate ventilation. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. Use explosion-proof ventilation equipment.

PERSONAL PROTECTION**EYE PROTECTION**

Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

GLOVES or HAND PROTECTION

The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection. Protective gloves are recommended to protect against contact with product. Polyvinyl alcohol, viton, safety 4H, teflon.

RESPIRATORY PROTECTION

Concentration in air determines the level of respiratory protection needed. Use only NIOSH certified respiratory equipment. Half-mask air purifying respirator with organic vapor cartridges is acceptable for exposures to ten (10) times the exposure limit. Full-face air purifying respirator with organic vapor cartridges is acceptable for exposures to fifty (50) times the exposure limit. Exposure should not exceed the cartridge limit of 1000 ppm. Protection by air purifying respirators is limited. Use a positive pressure-demand full-face supplied air respirator or SCBA for exposures greater than fifty (50) times the exposure limit. If exposure is above the IDLH (Immediately Dangerous to Life and Health) or there is the possibility of an uncontrolled release, or exposure levels are unknown, then use a positive pressure-demand full-face supplied air respirator with escape bottle or SCBA. Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

OTHER

Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required. The following materials are acceptable for use as protective clothing: polyvinyl alcohol (PVA), viton, polyurethane. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Remove contaminated clothing and wash before reuse. For non-fire emergencies, positive pressure SCBA and structural firefighter's protective clothing will provide only limited protection.

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

<u>PHYSICAL PROPERTY</u>	<u>TYPICAL</u>	<u>UNITS</u>	<u>TEXT RESULT</u>	<u>REFERENCE</u>
Appearance		N/A	COLORLESS LIQUID	
Boiling Point		F	278 TO 290	
Bulk Density		lb/gal	no data	
Melting Point		F	MINUS 53	
Molecular Weight		g/mole	no data	

Octanol/Water Coefficient		N/A	no data	
pH		N/A	no data	
Specific Gravity	0.87	N/A		
Solubility in Water		wt%	NIL	
Odor		N/A	SWEET, PLEASANT	
Odor Threshold		ppm	no data	
Vapor Pressure	9	mmHg		@25C
Viscosity (F)		SUS	no data	
Viscosity (C)		CsT	no data	
% Volatile	100	wt%		

Section 10. STABILITY AND REACTIVITY

STABILITY

Stable

CONDITIONS TO AVOID

Avoid static discharge

INCOMPATIBILITY

Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS

Combustion may produce carbon monoxide, carbon dioxide and other asphyxiants.

HAZARDOUS POLYMERIZATION

Will not polymerize.

Section 11. ECOLOGICAL INFORMATION

No data available

Section 12. DISPOSAL CONSIDERATIONS

Follow federal, state and local regulations. This material is a RCRA hazardous waste. Do not flush material to drain or storm sewer. Contract to authorized disposal service.

Section 13. TRANSPORT INFORMATION

<u>Governing Body</u>	<u>Mode</u>	<u>Proper Shipping Name</u>	<u>Container Mode</u>
DOT	Ground	Xylene, 3, UN1307, III	55 Gal Drum/5 Gal Pail
IATA	Air	unknown	
IMDG	Marine	unknown	

<u>Governing Body</u>	<u>Mode</u>	<u>Proper Shipping Name</u>	<u>Container Mode</u>
DOT	Ground	Consumer Commodity, ORM-D	Gallon/Quart
IATA	Air	unknown	
IMDG	Marine	unknown	

OTHER TRANSPORT INFORMATION

The DOT Transport Information may vary with the container and mode of shipment.

Section 14. REGULATORY INFORMATION

<u>Regulatory List</u>	<u>Component</u>	<u>CAS No.</u>
ACGIH-Occupational Exposure Limits - Carcinogens	XYLENE	1330-20-7
ACGIH-Occupational Exposure Limits -TWAs	XYLENE	1330-20-7
ACGIH-Short Term Exposure Limits	XYLENE	1330-20-7
CAA (Clean Air Act) - HON Rule - Organic HAPs	XYLENE	1330-20-7
CAA (Clean Air Act) - HON Rule - SOCM1 Chemicals	XYLENE	1330-20-7
CAA-1990 Hazardous Air Pollutants	XYLENE	1330-20-7
CERCLA/SARA-Haz Substances and their RQs	XYLENE	1330-20-7
CERCLA/SARA-Haz Substances and their RQs	XYLENE	1330-20-7

CERCLA/SARA-Haz Substances and their RQs	XYLENE	1330-20-7
CERCLA/SARA-Section 313-Emission Reporting	XYLENE	1330-20-7
CWA (Clean Water Act) - Hazardous Substances	XYLENE	1330-20-7
IARC - Group 3 (not classifiable)	XYLENE	1330-20-7
Inventory-Australia (AICS)	XYLENE	1330-20-7
Inventory-Canada-Domestic Substances List	XYLENE	1330-20-7
Inventory-China	XYLENE	1330-20-7
Inventory-European EINECS Inventory	XYLENE	1330-20-7
Inventory-Japan-(ENCS)	XYLENE	1330-20-7
Inventory-Korea-Existing and Evaluated	XYLENE	1330-20-7
Inventory-Philippines Inventory (PICCS)	XYLENE	1330-20-7
Inventory-TSCA-Sect.8(b) Inventory	XYLENE	1330-20-7
Massachusetts-Right To Know List	XYLENE	1330-20-7
New Jersey-Department of Health RTK List	XYLENE	1330-20-7
New Jersey-Env Hazardous Substances List	XYLENE	1330-20-7
New Jersey-Special Hazardous Substances	XYLENE	1330-20-7
OSHA-Final PELs-Time Weighted Averages	XYLENE	1330-20-7
Pennsylvania-RTK (Right to Know) List	XYLENE	1330-20-7
ACGIH - Occupational Exposure Limits - Carcinogens	BENZENE	71-43-2
ACGIH - Occupational Exposure Limits - Carcinogens	ETHYL BENZENE	100-41-4
ACGIH - Occupational Exposure Limits - Carcinogens	M-XYLENE	108-38-3
ACGIH - Occupational Exposure Limits - Carcinogens	O-XYLENE	95-47-6
ACGIH - Occupational Exposure Limits - Carcinogens	P-XYLENE	106-42-3
ACGIH - Occupational Exposure Limits - Carcinogens	TOLUENE	108-88-3
ACGIH - Occupational Exposure Limits - TWAs	BENZENE	71-43-2
ACGIH - Occupational Exposure Limits - TWAs	ETHYL BENZENE	100-41-4
ACGIH - Occupational Exposure Limits - TWAs	M-XYLENE	108-38-3
ACGIH - Occupational Exposure Limits - TWAs	O-XYLENE	95-47-6
ACGIH - Occupational Exposure Limits - TWAs	P-XYLENE	106-42-3
ACGIH - Occupational Exposure Limits - TWAs	TOLUENE	108-88-3
ACGIH-Short Term Exposure Limits	BENZENE	71-43-2
ACGIH-Short Term Exposure Limits	ETHYL BENZENE	100-41-4
ACGIH-Short Term Exposure Limits	M-XYLENE	108-38-3
ACGIH-Short Term Exposure Limits	O-XYLENE	95-47-6
ACGIH-Short Term Exposure Limits	P-XYLENE	106-42-3
ACGIH-Skin Absorption Designation	BENZENE	71-43-2
ACGIH-Skin Absorption Designation	TOLUENE	108-88-3
CAA (Clean Air Act) - HON Rule - Organic HAPs	BENZENE	71-43-2
CAA (Clean Air Act) - HON Rule - Organic HAPs	ETHYL BENZENE	100-41-4
CAA (Clean Air Act) - HON Rule - Organic HAPs	M-XYLENE	108-38-3
CAA (Clean Air Act) - HON Rule - Organic HAPs	O-XYLENE	95-47-6
CAA (Clean Air Act) - HON Rule - Organic HAPs	P-XYLENE	106-42-3
CAA (Clean Air Act) - HON Rule - Organic HAPs	TOLUENE	108-88-3
CAA (Clean Air Act) - HON Rule - SOCM1 Chemicals	BENZENE	71-43-2
CAA (Clean Air Act) - HON Rule - SOCM1 Chemicals	ETHYL BENZENE	100-41-4
CAA (Clean Air Act) - HON Rule - SOCM1 Chemicals	M-XYLENE	108-38-3
CAA (Clean Air Act) - HON Rule - SOCM1 Chemicals	O-XYLENE	95-47-6
CAA (Clean Air Act) - HON Rule - SOCM1 Chemicals	P-XYLENE	106-42-3
CAA (Clean Air Act) - HON Rule - SOCM1 Chemicals	TOLUENE	108-88-3
CAA - 1990 Hazardous Air Pollutants	BENZENE	71-43-2
CAA - 1990 Hazardous Air Pollutants	ETHYL BENZENE	100-41-4
CAA - 1990 Hazardous Air Pollutants	M-XYLENE	108-38-3
CAA - 1990 Hazardous Air Pollutants	O-XYLENE	95-47-6
CAA - 1990 Hazardous Air Pollutants	P-XYLENE	106-42-3
CAA - 1990 Hazardous Air Pollutants	TOLUENE	108-88-3
California-Prop. 65-Developmental Toxicity	BENZENE	71-43-2
California-Prop. 65-Developmental Toxicity	TOLUENE	108-88-3
California-Prop. 65-Reproductive-Male	BENZENE	71-43-2
California-Prop. 65-Carcinogens List	BENZENE	71-43-2
California-Prop. 65-Carcinogens List	ETHYL BENZENE	100-41-4
Canada-WHMIS-Ingredient Disclosure	BENZENE	71-43-2
Canada-WHMIS-Ingredient Disclosure	ETHYL BENZENE	100-41-4
Canada-WHMIS-Ingredient Disclosure	M-XYLENE	108-38-3

Canada-WHMIS-Ingredient Disclosure	O-XYLENE	95-47-6
Canada-WHMIS-Ingredient Disclosure	P-XYLENE	106-42-3
Canada-WHMIS-Ingredient Disclosure	TOLUENE	108-88-3
CERCLA/SARA-Haz Substances and their RQs	BENZENE	71-43-2
CERCLA/SARA-Haz Substances and their RQs	BENZENE	71-43-2
CERCLA/SARA-Haz Substances and their RQs	BENZENE	71-43-2
CERCLA/SARA-Haz Substances and their RQs	ETHYL BENZENE	100-41-4
CERCLA/SARA-Haz Substances and their RQs	ETHYL BENZENE	100-41-4
CERCLA/SARA-Haz Substances and their RQs	ETHYL BENZENE	100-41-4
CERCLA/SARA-Haz Substances and their RQs	M-XYLENE	108-38-3
CERCLA/SARA-Haz Substances and their RQs	M-XYLENE	108-38-3
CERCLA/SARA-Haz Substances and their RQs	M-XYLENE	108-38-3
CERCLA/SARA-Haz Substances and their RQs	O-XYLENE	95-47-6
CERCLA/SARA-Haz Substances and their RQs	O-XYLENE	95-47-6
CERCLA/SARA-Haz Substances and their RQs	O-XYLENE	95-47-6
CERCLA/SARA-Haz Substances and their RQs	P-XYLENE	106-42-3
CERCLA/SARA-Haz Substances and their RQs	P-XYLENE	106-42-3
CERCLA/SARA-Haz Substances and their RQs	P-XYLENE	106-42-3
CERCLA/SARA-Haz Substances and their RQs	TOLUENE	108-88-3
CERCLA/SARA-Haz Substances and their RQs	TOLUENE	108-88-3
CERCLA/SARA-Haz Substances and their RQs	TOLUENE	108-88-3
CERCLA/SARA-Section 313-Emission Reporting	BENZENE	71-43-2
CERCLA/SARA-Section 313-Emission Reporting	ETHYL BENZENE	100-41-4
CERCLA/SARA-Section 313-Emission Reporting	M-XYLENE	108-38-3
CERCLA/SARA-Section 313-Emission Reporting	O-XYLENE	95-47-6
CERCLA/SARA-Section 313-Emission Reporting	P-XYLENE	106-42-3
CERCLA/SARA-Section 313-Emission Reporting	TOLUENE	108-88-3
CWA (Clean Water Act) - Hazardous Substances	BENZENE	71-43-2
CWA (Clean Water Act) - Hazardous Substances	ETHYL BENZENE	100-41-4
CWA (Clean Water Act) - Hazardous Substances	M-XYLENE	108-38-3
CWA (Clean Water Act) - Hazardous Substances	O-XYLENE	95-47-6
CWA (Clean Water Act) - Hazardous Substances	P-XYLENE	106-42-3
CWA (Clean Water Act) - Hazardous Substances	TOLUENE	108-88-3
CWA (Clean Water Act) - Priority Pollutants	BENZENE	71-43-2
CWA (Clean Water Act) - Priority Pollutants	ETHYL BENZENE	100-41-4
CWA (Clean Water Act) - Priority Pollutants	TOLUENE	108-88-3
CWA (Clean Water Act) - Toxic Pollutants	BENZENE	71-43-2
CWA (Clean Water Act) - Toxic Pollutants	ETHYL BENZENE	100-41-4
CWA (Clean Water Act) - Toxic Pollutants	TOLUENE	108-88-3
IARC-Group 1 (carcinogenic to humans)	BENZENE	71-43-2
IARC-Group 2B (Possibly carcinogenic to humans)	ETHYL BENZENE	100-41-4
IARC-Group 3 (not classifiable)	TOLUENE	108-88-3
Inventory-Australia (AICS)	BENZENE	71-43-2
Inventory-Australia (AICS)	ETHYL BENZENE	100-41-4
Inventory-Australia (AICS)	M-XYLENE	108-38-3
Inventory-Australia (AICS)	O-XYLENE	95-47-6
Inventory-Australia (AICS)	P-XYLENE	106-42-3
Inventory-Australia (AICS)	TOLUENE	108-88-3
Inventory-Canada-Domestic Substances List	BENZENE	71-43-2
Inventory-Canada-Domestic Substances List	ETHYL BENZENE	100-41-4
Inventory-Canada-Domestic Substances List	M-XYLENE	108-38-3
Inventory-Canada-Domestic Substances List	O-XYLENE	95-47-6
Inventory-Canada-Domestic Substances List	P-XYLENE	106-42-3
Inventory-Canada-Domestic Substances List	TOLUENE	108-88-3
Inventory-China	BENZENE	71-43-2
Inventory-China	ETHYL BENZENE	100-41-4
Inventory-China	M-XYLENE	108-38-3
Inventory-China	O-XYLENE	95-47-6
Inventory-China	P-XYLENE	106-42-3
Inventory-China	TOLUENE	108-88-3
Inventory-European EINECS Inventory	BENZENE	71-43-2
Inventory-European EINECS Inventory	ETHYL BENZENE	100-41-4
Inventory-European EINECS Inventory	M-XYLENE	108-38-3

Inventory-European EINECS Inventory	O-XYLENE	95-47-6
Inventory-European EINECS Inventory	P-XYLENE	106-42-3
Inventory-European EINECS Inventory	TOLUENE	108-88-3
Inventory-Japan-(ENCS)	BENZENE	71-43-2
Inventory-Japan-(ENCS)	ETHYL BENZENE	100-41-4
Inventory-Japan-(ENCS)	M-XYLENE	108-38-3
Inventory-Japan-(ENCS)	O-XYLENE	95-47-6
Inventory-Japan-(ENCS)	P-XYLENE	106-42-3
Inventory-Japan-(ENCS)	TOLUENE	108-88-3
Inventory-Korea-Existing and Evaluated	BENZENE	71-43-2
Inventory-Korea-Existing and Evaluated	ETHYL BENZENE	100-41-4
Inventory-Korea-Existing and Evaluated	M-XYLENE	108-38-3
Inventory-Korea-Existing and Evaluated	O-XYLENE	95-47-6
Inventory-Korea-Existing and Evaluated	P-XYLENE	106-42-3
Inventory-Korea-Existing and Evaluated	TOLUENE	108-88-3
Inventory-Philippines Inventory (PICCS)	BENZENE	71-43-2
Inventory-Philippines Inventory (PICCS)	ETHYL BENZENE	100-41-4
Inventory-Philippines Inventory (PICCS)	M-XYLENE	108-38-3
Inventory-Philippines Inventory (PICCS)	O-XYLENE	95-47-6
Inventory-Philippines Inventory (PICCS)	P-XYLENE	106-42-3
Inventory-Philippines Inventory (PICCS)	TOLUENE	108-88-3
Inventory-TSCA-Sect.8(b) Inventory	BENZENE	71-43-2
Inventory-TSCA-Sect.8(b) Inventory	ETHYL BENZENE	100-41-4
Inventory-TSCA-Sect.8(b) Inventory	M-XYLENE	108-38-3
Inventory-TSCA-Sect.8(b) Inventory	O-XYLENE	95-47-6
Inventory-TSCA-Sect.8(b) Inventory	P-XYLENE	106-42-3
Inventory-TSCA-Sect.8(b) Inventory	TOLUENE	108-88-3
Massachusetts-Right To Know List	BENZENE	71-43-2
Massachusetts-Right To Know List	ETHYL BENZENE	100-41-4
Massachusetts-Right To Know List	M-XYLENE	108-38-3
Massachusetts-Right To Know List	O-XYLENE	95-47-6
Massachusetts-Right To Know List	P-XYLENE	106-42-3
Massachusetts-Right To Know List	TOLUENE	108-88-3
New Jersey-Department of Health RTK List	BENZENE	71-43-2
New Jersey-Department of Health RTK List	ETHYL BENZENE	100-41-4
New Jersey-Department of Health RTK List	M-XYLENE	108-38-3
New Jersey-Department of Health RTK List	O-XYLENE	95-47-6
New Jersey-Department of Health RTK List	P-XYLENE	106-42-3
New Jersey-Department of Health RTK List	TOLUENE	108-88-3
New Jersey-Env Hazardous Substances List	BENZENE	71-43-2
New Jersey-Env Hazardous Substances List	ETHYL BENZENE	100-41-4
New Jersey-Env Hazardous Substances List	M-XYLENE	108-38-3
New Jersey-Env Hazardous Substances List	O-XYLENE	95-47-6
New Jersey-Env Hazardous Substances List	P-XYLENE	106-42-3
New Jersey-Env Hazardous Substances List	TOLUENE	108-88-3
New Jersey-Special Hazardous Substances	BENZENE	71-43-2
New Jersey-Special Hazardous Substances	ETHYL BENZENE	100-41-4
New Jersey-Special Hazardous Substances	M-XYLENE	108-38-3
New Jersey-Special Hazardous Substances	O-XYLENE	95-47-6
New Jersey-Special Hazardous Substances	P-XYLENE	106-42-3
New Jersey-Special Hazardous Substances	TOLUENE	108-88-3
NTP-Report on Carcinogens-Known Carcinogens	BENZENE	71-43-2
OSHA-Final PELs-Ceiling Limits	BENZENE	71-43-2
OSHA-Final PELs-Ceiling Limits	TOLUENE	108-88-3
OSHA-Final PELs-Time Weighted Averages	BENZENE	71-43-2
OSHA-Final PELs-Time Weighted Averages	ETHYL BENZENE	100-41-4
OSHA-Final PELs-Time Weighted Averages	TOLUENE	108-88-3
OSHA-Regulated Carcinogens	BENZENE	71-43-2
OSHA-Select Carcinogens	BENZENE	71-43-2
Pennsylvania-RTK (Right to Know) List	BENZENE	71-43-2
Pennsylvania-RTK (Right to Know) List	ETHYL BENZENE	100-41-4
Pennsylvania-RTK (Right to Know) List	M-XYLENE	108-38-3
Pennsylvania-RTK (Right to Know) List	O-XYLENE	95-47-6

Pennsylvania-RTK (Right to Know) List	P-XYLENE	106-42-3
Pennsylvania-RTK (Right to Know) List	TOLUENE	108-88-3
Pennsylvania-RTK-Special Hazardous Substances	BENZENE	71-43-2
TSCA-Sect. 12(b)-Export Notification	P-XYLENE	106-42-3
TSCA-Section 4-Chemical Test Rules	P-XYLENE	106-42-3
TSCA-Section8(a)-PAIR Reporting List	P-XYLENE	106-42-3

Title III Classifications Sections 311, 312:

Acute:	YES
Chronic:	YES
Fire:	YES
Reactivity:	NO
Sudden Release of Pressure:	NO

Section 15. OTHER INFORMATION

COMPONENT TOXICITY: Ethylbenzene, a component of this product, has been designated by the International Agency for Research on Cancer as "possibly carcinogenic to humans", based on increased tumor incidence in laboratory animals. Overexposure may lead to nervous system effects, including drowsiness, dizziness, nausea, headaches, paralysis, loss of consciousness and even death. Repeated overexposure has caused a hearing loss in laboratory animals. NOTE TO PHYSICIAN: Catecholamines and similar adrenergic drugs are generally contraindicated because of potential for increased sensitivity of the heart from hydrocarbon overexposure and subsequent ventricular fibrillation. EKG monitoring may be indicated and bronchodilators should be selected with care. Following injection, prompt debridement of the wound is necessary to minimize necrosis and tissue loss. Follow all MSDS/label precautions even after container is emptied because it may retain product residue.

E.E. Zimmerman Company/Elroy Turpentine Company believes that the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.